


TECHNISCHES DATENBLATT

TECHNICAL DATA SHEET



Außenmaße inkl. Füße – B x T x H Outer dimensions incl. feet – W x D x H	1200 x 1100 x 630 mm	1200 x 1100 x 760 mm	1200 x 1100 x 850 mm
Innenmaße – B x T x H Inner dimensions – W x D x H	1120 x 1020 x 476 mm	1120 x 1020 x 606 mm	1120 x 1020 x 696 mm
Modell / Version	CT/L 630	CT/L 760	CT/L 850
Nennvolumen Nominal volume	570 L	730 L	830 L
Zul. Bruttogewicht – Feststoffe Max. permitted gross weight–solids	350 kg	480 kg	550 kg
Eigengewicht +/- 5 % / Net weight +/- 5 % Box mit 4 Füßen (offen) / Box with 4 feet (open)	33 kg	38 kg	40,6 kg
Box mit 2 Traversen (offen) / Box with 2 runners (open)	35,2 kg	40,2 kg	42,8 kg
Max. zul. Füllgewicht – Feststoffe im „stand-alone“-Betrieb am Boden Max. „stand-alone“ weight allowance (without stacking) for solids	1400 kg	1440 kg	1650 kg
Volle LKW-Ladung / full truck load Standard: 13,6 x 2,65 m Jumbo: 15,4 x 2,95 m	96 Stk./pcs. 140 Stk./pcs.	96 Stk./pcs. 140 Stk./pcs.	96 Stk./pcs. 140 Stk./pcs.
Container 20' HC: 5,90 x 2,35 x 2,68 m Container 40' HC: 12,03 x 2,35 x 2,68 m	38 Stk./pcs. 82 Stk./pcs.	38 Stk./pcs. 82 Stk./pcs.	38 Stk./pcs. 82 Stk./pcs.
Max. Stapellast bei 5° C Max. stacking load at 5° C	Max. Belastung im Stapel darf nicht überschritten werden; ebener, druckfester und windgesicherter Stand wird vorausgesetzt! Max. load in stack must not be exceeded; flat surface, pressure-resistant floor and wind-protected stand is required!		
	4.200 kg*	4.800 kg*	3.300 kg*
Standardfarben / Standard colours			
Material / Material	PE (Polyethylene)		
Recyclebar / Recyclable	100 %		
Chemische Resistenz Chemical resistance	Hoch / High		
Lebensmittelecht Food safe	Ja / Yes		
Standardeinsatztemperatur Standard operating temp.	-20° C – +40° C (bei / at +40° C = reduzierte Stapellast / reduced stacking load)		
Güte und Prüfbestimmung Quality requirements	Interne Prüfung / internal audit		